

Serial No.: 10/718,391

IN THE CLAIMS:

Please cancel claims 7-9, 16-18, and 27-31 without prejudice or disclaimer and amend the remaining claims as follows:

1. (currently amended) An ~~apparatus~~ cold plate for cooling an electronic component, comprising:
 - a first member defining a first set of semi-circular channel walls, the first set of channel walls having a first channel gap between two respective facing walls of the first set of channel walls;
 - a second member defining a second set of semi-circular channel walls, the second member being coupled to the first member such that the second set of channels walls are interlaced with the first set of channel walls;
 - a fluid inlet provided on one of the first and second members; and
 - a fluid outlet provided on one of the first and second members,wherein a channel structure defined by the first and second sets of channel walls provides at least two fluid flow paths having different flow directions between the fluid inlet and the fluid outlet.
2. (currently amended) The ~~apparatus~~ cold plate of claim 1, wherein a second channel gap between two respective facing walls of the interlaced first and second sets of channel walls is narrower than the first channel gap.

Serial No.: 10/718,397

3. (currently amended) The ~~apparatus~~ cold plate of claim 1, wherein a the channel structure defined by the first and second sets of channel walls provides ~~at least two~~ substantially symmetrical fluid flow paths between the fluid inlet and the fluid outlet.

4. (currently amended) The ~~apparatus~~ cold plate of claim 1, wherein a the channel structure defined by the first and second sets of channel wall provides ~~primarily four~~ non-linear flow paths having different flow directions between the fluid inlet and the fluid outlet.

5. (currently amended) The ~~apparatus~~ cold plate of claim 1, wherein ~~the first member includes a first index feature which cooperates with a corresponding second index feature on the second member to aid in aligning the first and second members with respect to each other~~ fluid inlet is located at a center of the cold plate.

6. (currently amended) The ~~apparatus~~ cold plate of claim 1, wherein a surface of a wall of the first set of channel walls is tapered at an angle of greater than about five degrees.

7-9. (canceled).

Serial No.: 10/718,397

10. (currently amended) A method, comprising:

forming a first member defining a first set of semi-circular channel walls, the first set of channel walls having a first channel gap between two respective facing walls of the first set of channel walls;

forming a second member defining a second set of semi-circular channel walls;

coupling the second member to the first member such that the second set of channels walls are interlaced with the first set of channel walls;

providing a fluid inlet on one of the first and second members; and

providing a fluid outlet on one of the first and second members; and

providing at least two fluid flow paths having different flow directions between the fluid inlet and the fluid outlet.

11. (original) The method of claim 10, wherein a second channel gap between two respective facing walls of the interlaced first and second sets of channel walls is narrower than the first channel gap.

12. (currently amended) The method of claim 10, further comprising:

providing at least two substantially symmetrical fluid flow paths between the fluid inlet and the fluid outlet.

Serial No.: 10//18,397

13. (currently amended) The method of claim 10, further comprising:
providing primarily four non-linear flow paths having different flow directions between the fluid inlet and the fluid outlet.

14. (currently amended) The method of claim 10, further comprising:
~~providing a first index feature on the first member;~~
~~providing a second index feature on the second member; and~~
~~aligning the first and second members in accordance with the first~~
~~and second index features~~
providing the fluid inlet at a center of one of the first and second
members.

15. (original) The method of claim 10, further comprising:
tapering a surface of a wall of the first set of channel walls at an
angle of greater than about five degrees.

16-18. (canceled).

Serial No.: 10/718,397

19. (currently amended) A system, comprising:

an electronic component; and

a cold plate thermally coupled to the electronic component, the cold plate comprising:

a first member defining a first set of semi-circular channel walls, the first set of channel walls having a first channel gap between two respective facing walls of the first set of channel walls;

a second member defining a second set of semi-circular channel walls, the second member being coupled to the first member such that the second set of channels walls are interlaced with the first set of channel walls;

a fluid inlet provided on one of the first and second members; and

a fluid outlet provided on one of the first and second members,

wherein a channel structure defined by the first and second sets of channel walls provides at least two fluid flow paths having different flow directions between the fluid inlet and the fluid outlet.

20. (original) The system of claim 19, wherein a second channel gap between two respective facing walls of the interlaced first and second sets of channel walls is narrower than the first channel gap.

Serial No.: 10/718,397

21. (currently amended) The system of claim 19, wherein a channel structure defined by the first and second sets of channel walls provides at least two substantially symmetrical fluid flow paths between the fluid inlet and the fluid outlet.

22. (currently amended) The system of claim 19, wherein a channel structure defined by the first and second sets of channel wall provides primarily four non-linear flow paths having different flow directions between the fluid inlet and the fluid outlet.

23. (currently amended) The system of claim 19, wherein the ~~first member includes a first index feature which cooperates with a corresponding second index feature on the second member to aid in aligning the first and second members with respect to each other~~ fluid inlet is located at a center of the cold plate.

24. (original) The apparatus of claim 19, wherein a surface of a wall of the first set of channel walls is tapered at an angle of greater than about five degrees.

Serial No.: 10/718,397

25. (original) The system of claim 19, further comprising:
a heat dissipation device coupled to the cold plate by a loop of
tubing;

cooling fluid disposed in the tubing; and
a pump adapted to circulate the cooling fluid.

26. (original) The system of claim 25, further comprising:
a fan adapted to provide cooling air to at least one of the heat
dissipation device and the cold plate.

27-31. (canceled).